

Straight Wall Tote Specifications:



UPM-NSO 1215-09



UPM-NSO 2415-14

Model	Outside Dimensions		Inside Dimensions		Total Height (inches)	Product Clearance		Weight		Volume (cubic feet)	Trailer Qty* (53' trailer)
	L (inches)	W (inches)	L (inches)	W (inches)		Flat	Cross Stack	Flat	Cross Stack		
UPM-NOS 1207-05 Only available in flat bottom	12.0	7.0	9.4	5.5	5.0	4.5	N/A	1.3	N/A	0.1	13,104
UPM-NSO 1215-04	12.0	15.0	9.4	13.0	4.0	3.4	2.9	1.6	1.8	0.2	8,112
UPM-NSO 1215-05	12.0	15.0	9.4	13.0	5.0	4.4	3.9	1.7	2.0	0.3	6,552
UPM-NSO 1215-07	12.0	15.0	9.5	13.1	7.5	6.9	6.4	2.3	2.6	0.5	4,056
UPM-NSO 1215-09	12.0	15.0	9.4	13.0	9.5	8.9	8.4	2.7	2.9	0.7	3,120
UPM-NSO 2415-05	24.0	15.0	21.5	13.1	5.0	4.4	3.9	2.9	3.4	0.7	3,120
UPM-NSO 2415-07	24.0	15.0	21.5	13.1	7.4	6.8	6.3	3.7	4.2	1.1	2,028
UPM-NSO 2415-09	24.0	15.0	21.5	13.1	9.5	8.9	8.4	4.3	4.8	1.4	1,560
UPM-NSO 2415-11	24.0	15.0	21.4	13.0	10.8	10.2	9.7	4.7	5.3	1.7	1,404
UPM-NSO 2415-14	24.0	15.0	21.5	13.1	14.5	13.9	13.4	5.7	6.3	2.3	936
UPM-NSO 2422-07	24.0	22.0	21.5	20.6	7.4	6.8	6.3	4.9	5.6	1.7	1,352
UPM-NSO 2422-09	24.0	22.0	21.5	20.6	9.5	8.9	8/4	5.6	6.3	2.1	1,040
UPM-NSO 2422-11	24.0	22.0	21.4	20.5	10.8	10.2	9.7	6.1	6.8	2.6	936
UPM-NSO 2422-14	24.0	22.0	21.4	20.5	14.5	13.9	13.4	7.4	8.0	3.5	624
UPM-1215-Lid	12.0	15.0	N/A	N/A	0.9	N/A		0.9		N/A	31,200
UPM-2415-Lid	24.0	15.0	N/A	N/A	0.9	N/A		1.5		N/A	13,780

*Quantities when packed out as a unitized load with AIAG pallet and top cap

Manufacturing Pallet Specifications:



UPM-SP 4845-5-IMW-I

Model	Entry	Outside Dimensions			(lbs)	Static Load		Nest Ratio	Stack Qty	Trailer Qty* (53' trailer)
		L (inches)	W (inches)	H (inches)		(lbs)	(lbs)			
UPM-SP 4845-5-IMW-I	4-Way	48.0	45.0	5.0	50.0	30,000	4,000	1:1	21	546
UPM-TC 4845-3-IM-II	N/A	48	45	2.6	16.0	N/A	N/A	N/A	50	1,170
UPM-NP 4845-6-SF-II	4-Way	48.0	45.8	5.8	36.0	30,000	2,000	1.96:1	35	910
UPM-TC 4845-3-IM-III	N/A	48.9	45.9	2.6	14.1	N/A	N/A	N/A	67	1,742

Manufacturing Pallets are not intended to be racked.

Contact your Universal sales representative to discuss your application and maximum load ratings for all products.